

HVR-7200 Quick Easy IV High Definition video recorder

www.meicheng.com.tw







Feature

- Support stand-along mode to record video; support various types USB flash drive, external hard drive (Maximum storage capacity: 2TB), Press one button to record/stop.
- Supports various input signals including HDMI, VGA, AV and with an included MMI cable.
- Support HDMI output port, records while you are playing games or enjoying favorite videos without interruption.
- Support transfer VGA, AV, YPbPr and L/R stereo audio input signals to HDMI output, and can enhance video resolution.
- Support plug and Play, easy operating.
- Support any lower than 1080P video resolution to enhance to 1080P resolution to recording and watching, effectively improve video quality.
- Support instant video playback after recording, can viewing the video files in USB flash drive and external hard drive.
- Support 2K/4K resolution input source, recording file will be 1080P 30 frames per second.
- Adopts advanced hardware H.264 encoding to capture your video in stunning 1080p Full HD,
- Schedule Recording Set the start time, recording time and recording frequency, and then videos will be recorded automatically.
- Support continuity recording if the input signal been interrupted accidentally.
- Equipped USB interface to connect with PC, support to using as capture card, and can watching and recording video on PC.
- Support AMCAP, OBS, OBS studio, Xsplit, Potplayer, QQ video conference streaming software...etc. While using as video capture card.

(Notes)

HVR-7200 high definition video recorder support connect with USB flash drive or external hard drive to storage, also can capture video from PC, using as USB 3.0 video capture card, delay time around 2 seconds. Equipped with software for screenshots, videos, previews and local live streaming. Support AMCAP, OBS, OBS studio, Xsplit, Potplayer, QQ video conference streaming software···etc.

Specification


| Input port | HDMI \times 1,YPbPr \times 1,VGA \times 1,CVBS \times 1 \cdot RCA L/R stereo audio, microphone input \times 1 |
|-------------------------|---|
| Output port | HDMI \times 1,USB \times 1 (USB2.0/3.0,writing speed>10MB/s) ,USB to PC \times 1,audio outpur \times 1 |
| Video signal formats | $\label{eq:hdminus} \begin{split} \text{HDMI Video}: 480i/p &\sim 576i/p &\sim 720p &\sim 1080i &\sim 1080p \ 50/60 \ \text{Hz} \ 1440p &\sim 2160p \ 30/60 \ \text{Hz} \\ \text{Component Video}: 480i/p &\sim 576i/p &\sim 720p &\sim 1080i/p \ 50/60 \ \text{Hz} \\ \text{DVI/VGA Video}: 800 \times 600 &\sim 1024 \times 765 &\sim 1280 \times 1024 &\sim 1440 \times 900 &\sim 1680 \times 1050 &\sim 1920 \times 1080 \ 50/60 \ \text{hz} \ (\text{RGB}) \\ \text{Video standards}: \text{PAL/NTSC} \end{split}$ |
| Audio signal | Maximum 16bit 48khz L/R stereo (via HDMI port) |
| Capture resolution | 720×480~1920×1080 30~60 frames per second (Under 1080i/p resolution: 25/30 frames per second, the rest of mode:50/60 frames per second) |
| Encoding format | H.264+AAC Hardware compression, output file: mp4 format, capacity around 10mins for 1G ,USB flash drive support FAT/FAT32 format, external hard drive support FAT/FAT32/NTFS format(not support EXFAT format) |
| Dimesions | 146×150×20mm |

Application



Mode 2 Connecting with USB port of PC, use as capture card





Meicheng® MEI CHENG AUDIO VIDEO CO., LTD.

Address: 13F., No.2, Jian 8th Rd., Zhonghe Dist., New Taipei City 235, Taiwan Tel: +886(2) 8228 0311, Fax: +886(2) 8228 0319
Website: www.meicheng.com.tw Email:mei.cheng@msa.hinet.net